



# LTKD/LTMD

Model	Allowable Torque (Nm)	Allowable Thrust (KN)	Allowable Valve Rod Diameter (mm)		Sleeve Rotation Speed min-1 (50/60Hz)	Motor	
			Non-Rising	Rising		Power Supply	kW
LTKD-01 LTMD-01	250	45	28	30	10.6/12.6 ~71.3/85.5	200V50/60Hz 400V50/60Hz	0.2, 0.4 0.75
LTKD-02 LTMD-02	450	65	40	42	10.5/12.7 ~66.0/79.2	220V60Hz 440V60Hz	0.4, 0.75 1.5
LTKD-05 LTMD-05	850	105	50	75	14.8/17.8 ~71.3/85.5		0.4, 0.75 1.5, 2.2, 3.7
LTKD-1 LTMD-1	1,750	200	62	70	9.3/11.2 ~66.0/79.2		1.5, 2.2 3.7, 5.5
LTKD-3 LTMD-3	4,000	320	80	90	8.0/9.6 ~64.5/77.4		3.7, 5.5 7.5, 11
LTKD-5 LTMD-5	6,500	500	100	115	10.7/12.9 ~61.2/73.4		5.5, 7.5 11, 15
LTKD-10B LTMD-10B	12,000	1,100	115	135	10.6/12.8 ~63.1/75.7		7.5, 11 15, 18.5

\*Dimensions and shape are subject to slight change without notice.

